


# MATERIAL SAFETY DATA SHEET and WARRANTY

B644B-0B12

Date: February 12, 2010

## Section I Identification



HEALTH	[2*]
FLAMMABILITY	[3]
REACTIVITY	[0]
PROTECTION	[H]

Product Name:	<b>SCOFIELD® Revive™ Color Refresher Part B (Base)</b>
Chemical Name:	<b>Mixture</b>
Chemical Family:	<b>Colored Waterproofing Treatment</b>
Chemical Formula:	<b>Mixture</b>
Emergency Telephone Number:	<b>CHEMTREC (800) 424-9300</b>
Telephone Number for Information:	<b>SCOFIELD (770) 920-6000 (323) 720-3000</b>

## Section II Composition/ Information on Ingredients

Composition	Weight	OSHA PEL	ACGIH TLV	CAS Number
<b>**2-Propanone, Acetone</b>	<b>60–90%</b>	<b>750 ppm</b>	<b>750 ppm</b>	<b>67-64-1</b>
<b>* Aromatic Hydrocarbon</b>	<b>1–10%</b>	<b>10 ppm</b>	<b>10 ppm</b>	<b>64742-94-5</b>
<b>*Aromatic Petroleum Distillates</b>	<b>1–10%</b>	<b>100 ppm</b>	<b>N/A</b>	<b>64742-95-6</b>
<b>+Trimethylbenzene</b>	<b>1–5%</b>	<b>25 ppm</b>	<b>25 ppm</b>	<b>95-63-6</b>

\* Chemical(s) that are chronic health hazards. Refer to *Section III–Hazards Identification* for further information.  
+ Toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

## Section III Hazards Identification

Primary Routes of Exposure:	<b>Skin contact, eye contact, and inhalation.</b>
Effects of Acute Exposure:	<p>Eyes — <b>Contact with eyes may cause irritation including burning, watering, and redness.</b></p> <p>Skin — <b>Contact may cause mild skin irritation including redness, burning, and drying and cracking of skin. Continued exposure may develop into dermatitis. Solvents can penetrate the skin and cause systematic effects similar to those under <i>Inhalation</i> symptoms.</b></p> <p>Inhalation — <b>High vapor concentrations are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, asthma, drowsiness, unconsciousness, and other central nervous system effects, and possibly death.</b></p> <p>Ingestion — <b>Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury.</b></p>
Chronic Health Effects:	<b>Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as Solvent or Painter's Syndrome). Intentional misuse by deliberately concentrating and inhaling this material may be harmful or fatal. Chronic exposure may also cause damage to the respiratory system, lungs, eyes, skin, gastrointestinal tract, liver, spleen and kidneys. Repeated skin contact may cause persistent irritation or dermatitis.</b>
Medical Conditions Generally Aggravated by Exposure:	<b>Conditions aggravated by exposure may include skin disorders, respiratory (asthma-like) disorders, and pre-existing liver or kidney conditions.</b>

# MATERIAL SAFETY DATA SHEET and WARRANTY

Date: February 12, 2010

SCOFIELD® Revive™ Color Refresher – Part B

## Section IV First Aid Measures

### Emergency and First Aid Procedures:

Eyes — **OBJECT IS TO FLUSH MATERIAL OUT IMMEDIATELY THEN GET MEDICAL ATTENTION.** Flush IMMEDIATELY with lukewarm water while holding eyelids apart. Flushing within several seconds is essential to achieve maximum effectiveness. If physician is not immediately available, continue flushing with water.

Inhalation — **If breathing becomes difficult, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.**

Ingestion — **Do not induce vomiting. Vomiting will cause further damage to the throat. Give conscious victim 1 to 2 glasses of water. If spontaneous vomiting occurs, have victim lean forward with head down to avoid breathing in of vomitus, rinse mouth and administer more water. Contact local poison control center. Immediately transport victim to an emergency facility. Never give anything by mouth if victim is losing consciousness, or is unconscious or convulsing.**

Skin — **Wash thoroughly with soap and water. Remove soiled clothing and footwear and wash before reuse. If irritation occurs, get medical attention.**

## Section V Fire and Explosion Hazard Data

Flash Point (Method Used): -15° F (TCC)

Flammable Limits (% in Air by Volume): Lower – 1.0 Upper – 12.8

Extinguishing Media: **Foam, CO<sub>2</sub>, or dry chemical is recommended. Water spray is recommended to cool or protect exposed materials or structures.**

Special Fire Fighting Procedures: **Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters. Carbon dioxide can displace oxygen; exercise caution when using CO<sub>2</sub> in confined areas.**

Unusual Fire and Explosion Hazards: **Vapors may be ignited by heat, sparks, flames, or other sources of ignition. Vapors are heavier than air and may travel considerable distances to a source of ignition where they may cause a flashback or explosion. If container is not properly cooled, it can rupture in the presence of excessive heat.**

## Section VI Accidental Release Measures

Steps to Be Taken in Case Material is Released or Spilled: **Keep all sources of ignition and hot metal surfaces away from spill/release. Use explosion-proof non-sparking equipment. Stay upwind from area. Isolate danger and keep unauthorized personnel out. Stop source of release if possible with minimal risk. Wear appropriate protective equipment including respiratory protection. Prevent spill from entering sewers, storm drains, or any other unauthorized treatment drainage systems and natural waterways by diking ahead of the spill. Spilled material may be absorbed with an appropriate spill kit. Notify fire authorities and appropriate federal, state, and local agencies if required.**

## Section VII Handling and Storage

Handling Information: **Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Open container slowly to relieve any pressure. Bond and ground all equipment when transferring from one vessel to another. Static charge can accumulate by flow or agitation. Ignition can occur by static discharge. The use of explosion-proof equipment is recommended and may be required. The use of respiratory protection is advised when concentrations exceed any established exposure limits and in confined spaces. Use good industrial and personal hygiene practice, wash thoroughly after handling, and do not wear contaminated clothing.**

Storage Information: **Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see Section X—Stability and Reactivity). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.**

# MATERIAL SAFETY DATA SHEET and WARRANTY

Date: February 12, 2010

SCOFIELD® Revive™ Color Refresher – Part B

## Section VII Handling and Storage (continued)

Other Precautions: **“Empty” containers retain residue, liquid and vapor, and may be dangerous. Do not cut, weld, pressurize, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause severe personal injury or death. All containers should be disposed of in an environmentally safe manner in accordance with all government regulations.**

## Section VIII Control Measures/ Personal Protection

Respiratory Protection: **Engineering or administrative controls should be implemented to reduce exposure. A NIOSH/MSHA approved respirator with an organic vapor cartridge should be used under conditions where airborne concentrations are expected to exceed exposure limits (see Section II). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.**

Ventilation: **If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, electrical systems safe for such locations must be used.**

Protective Gloves: **Prevent prolonged or repeated contact by wearing gloves impervious to solvents and other appropriate protective clothing. Launder contaminated clothing before reuse.**

Eye Protection: **Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.**

Other Protective Clothing or Equipment: **A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.**

Work/Hygienic Practices: **Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up spills promptly. Follow OSHA and company guidelines.**

## Section IX Physical and Chemical Properties

Physical State:	<b>Liquid</b>	Color:	<b>Clear (water white)</b>
Odor:	<b>Hydrocarbon odor</b>	Solubility in Water:	<b>Insoluble/Negligible</b>
Specific Gravity (H <sub>2</sub> O = 1):	<b>Approximately 0.85</b>	Vapor Density:	<b>Heavier than air</b>
Boiling Range:	<b>133° F–363° F</b>	Evaporation Rate:	<b>Faster than nBuAc</b>
Volatile Organic Compounds:	<b>Low-solids coating. Material VOC less than 120 g/L (1.0 lb/gal).</b>		

## Section X Stability and Reactivity

Stability:	<b>Stable under normal conditions and handling.</b>
Conditions to Avoid:	<b>All possible sources of ignition.</b>
Incompatibility (Materials to Avoid):	<b>Avoid exposure to strong oxidizing agents and reducing agents.</b>
Hazardous Decomposition or By-products:	<b>Combustion may liberate toxic by-products such as carbon dioxide, carbon monoxide, various oxides of carbon and nitrogen.</b>
Hazardous Polymerization:	<b>Will not occur.</b>

## Section XI Toxicological Information

Sensitization:	<b>None known.</b>
Carcinogenicity:	<b>There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.</b>
Reproductive Toxicity:	<b>There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.</b>

# MATERIAL SAFETY DATA SHEET and WARRANTY

Date: February 12, 2010

SCOFIELD® Revive™ Color Refresher – Part B

## Section XI Toxicological Information (continued)

Teratogenicity (Birth Defects): **There is no data available to indicate any components present at greater than 0.1% may cause birth defects.**

Mutagenicity: **There is no data to indicate that any component present at greater than 0.1% will alter DNA.**

## Section XII Ecological Information

Environmental Data:

**Although no information is available for this specific product mixture, individual components may by themselves have ecological affects. Trimethylbenzene is a marine pollutant under 49 CFR 172.101.**

## Section XIII Disposal Considerations

**This product is considered a RCRA hazardous waste due to the characteristic(s) of D001 (ignitability). Waste is subject to the land disposal restrictions in 40 CFR 268.40 and may require treatment standards. Consult state and local regulations to determine whether they are more stringent than the federal requirements.**

**Container contents should be completely used and containers empty prior to discarding. Container rinsate could be considered a RCRA hazardous waste and must be discarded in compliance with all applicable regulations. Larger empty containers, such as drums, should be returned to a professional drum reconditioner. To assure proper disposal of smaller empty containers, consult with state and local regulations and disposal authorities.**

## Section XIV Transportation Information

Proper DOT Shipping Name:  
**UN1139, Coating Solution, 3, II**

## Section XV Regulatory Information

**ALL INGREDIENTS OF THIS PRODUCT ARE LISTED, OR ARE EXCLUDED FROM LISTING, ON THE U.S. TOXIC SUBSTANCES CONTROL ACT (TSCA) CHEMICAL SUBSTANCE INVENTORY.**

**This product does contain a chemical(s) subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372). See *Section II—Composition/Information on Ingredients*.**

State Specific Requirements:

**State of California *Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)*;  
WARNING: This product contains a chemical known to the State of California to cause cancer, or birth defects or other reproductive harm.**

State Listed Components	CAS Number	State Code
Acetone	67-64-1	CA,CT,FL,IL,LA,ME,MN,NJ,PA,RI
Trimethylbenzene	95-63-6	CA,MA,MN,NJ,PA

## Section XVI Other Information

Before using this product:

**Completely read Scofield's Tech-Data Bulletin *B-644 SCOFIELD Revive Color Refresher* and the container label.**

## WARRANTY

Since no control is exercised over product use, L. M. Scofield Company (Scofield) represents and warrants only that its products are of consistent quality within manufacturing tolerances. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESS OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SCOFIELD, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Liability for breach of contract, negligence, or on any other legal basis is limited to the lesser of refund or replacement of defective materials. SCOFIELD WILL NOT BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING FOR DELAYS OR LOST PROFITS. Communication of this warranty and its limitations to end users is not the responsibility of Scofield, but should be communicated by those in direct contract with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. The end user shall determine the suitability of the products for the intended use and assumes all risks and liability in connection therewith.