

# SCOFIELD® Liquid Release BG

Clear liquid bond breaker used with stamping mats, texturing skins or texture rollers prior to imprinting concrete or cementitious overlays.



A SIKA BRAND

## 1. Product Description:

SCOFIELD® Liquid Release BG is a bond breaker used with stamping mats, texturing skins or texture rollers prior to imprinting concrete or cementitious overlays. It prevents the stamping or texturing tool from sticking to the surface, enhances the transfer of the detailed pattern and texture, and prolongs the surface life of the stamping mat or texturing tool. Use on integrally colored or uncolored concrete, shake-on color hardeners, and stampable cementitious overlays. It is suitable for outdoor and indoor use. It is particularly useful with overlays, since it will not contaminate the existing concrete substrate as readily as powdered releases. It evaporates quickly and requires little to no clean up prior to applying solvent based curing and sealing compounds such as SCOFIELD® Cureseal™ 700, or prior to chemical staining with LITHOCHROME® Chemstain® Classic.

## 2. Packaging:

SCOFIELD® Liquid Release BG is available in 5 gal. (19 L) pails. Pails should be stored in a cool, dry place when not in use. Store away from combustible materials and sources of heat. Do not reuse empty container.

### 2.1. Shelf Life:

Indefinite, when stored in original, unopened containers, in dry storage.

## 3. Coverage:

A 5 gal. pail covers approximately 750 sq. ft. (1 1/3.7 m<sup>2</sup>) of concrete surface. Apply full strength. Do not dilute. Coverage will vary depending on timing, surface finish prior to stamping, application method, air temperature, humidity and wind conditions. Conditioning of the stamping tools with the liquid release prior to stamping will also affect the amount of material used.

## 4. Application Equipment:

A clean, quality hand-pump sprayer equipped with a fan pattern spray nozzle should be used to apply SCOFIELD® Liquid Release BG. Material should be applied to the surface of the concrete and to the pattern and texturing tools. Spraying equipment must be resistant to solvent-based materials.

## 5. Application:

Apply SCOFIELD® Liquid Release BG after all finishing is completed and prior to imprinting the surface. Do not attempt to float, trowel, or otherwise work the surface once the liquid release is applied. Do not apply over a large area, as the liquid release may evaporate prior to the imprinting process. Do not apply if bleed water is visible on the concrete surface. Material should also be applied to the imprinting tools.

Apply liberally. SCOFIELD® Liquid Release BG evaporates and it must be reapplied to the concrete surface and tools during the imprinting process. Do not attempt to imprint the surface without liquid release visible on the concrete or imprinting tool surface. After complete evaporation, the concrete surface will lose its wet sheen and appear dull. At this time, the surface may be cured or sealed with SCOFIELD® Cureseal™ 700, or chemically stained with LITHOCHROME® Chemstain® Classic in accordance with

the Technical Data Sheets for those products. All information is available for download online at [www.scofield.com](http://www.scofield.com) or at 800-800-9900.

## 6. Quality Control:

Cast a job site sample at least 21 days prior to the installation for approval of color and finish. Utilize all materials, tools, and techniques from the actual job in the mock-up. Consistent batching, pouring, finishing, curing, sealing, and preparation techniques, will ensure the uniformity of architectural concrete. Verify adequate wet and dry slip resistance. Verify maintenance requirements. Site visits by Scofield personnel are for making technical recommendations only and not for supervising or providing quality control.

## WARRANTY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at <http://usa.sika.com/> or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <http://usa.sika.com/> or by calling Sika's Technical Service Department at 800-933-7452. **Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Product Data Sheet, product label and Safety Data Sheet prior to product use.**

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY**



**OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**



A SIKA BRAND

■ Scofield customer service: 1 800 800 9900  
4155 Scofield Road, Douglasville, GA 30134 voice: 770 920 6000 fax: 770 920 6060

[www.scofield.com](http://www.scofield.com)