

# SCOFIELD® Acrylic Sealer 25-700

Pure acrylic concrete sealers in a solvent base

TECH-DATA BULLETIN TD-XXXX.01

Rev. 01.11.2018



BUILDING TRUST



## 1. Description:

**SCOFIELD Acrylic Sealer 25-700** is a tough pure acrylic concrete sealer in a solvent base. It is designed to protect and beautify all types of concrete with a high gloss durable clear coating. Also available in MATTE finish. SCOFIELD Acrylic Sealer 25-700 is non-yellowing to preserve the appearance of all types of decorative concrete.

## 2. Preparation:

Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or Pressure washer similar solvent-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with Clemons' CLEANER DEGREASER NEUTRALIZER. Use a bristle brush for heavily oiled spots. If surface is slick, etch with Clemons' ETCH & CLEAN. Rinse well with a pressure washer. Allow 24 hours to dry. Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause bubbles to form. For pavers, sweep away any loose sand. **DO NOT THIN.**

## 3. Application:

Brush may be used where roller won't reach. Do not pour directly from can to concrete. Apply evenly from can or other metal container with appropriate roller. Use a long nap roller for exposed aggregate, a medium nap roller for textured surfaces and a short nap roller for smooth surfaces. Wait until the surface is tack-free before applying a second coat. Apply perpendicular to the first coat. Cross-rolling allows for an even application. If spraying, use a solvent resistant sprayer holding tip no more than 8" from surface during application. Back rolling is recommended while spraying. Clean up immediately with A-1 SOLVENT, Xylene or Acetone. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Cooler temperatures or increased humidity will slow the dry time.

## 4. Net Rate Coverage:

Two thin coats are recommended for net coverage of:

Smooth Troweled:	300 ft <sup>2</sup> per gallon	Textured or Stamped:	200 ft <sup>2</sup> per gallon
Broom Swept:	200 ft <sup>2</sup> per gallon	Exposed Aggregate and Pavers:	100 ft <sup>2</sup> per gallon

## 5. Slip Resistance:

For additional slip resistance, apply one coat of SCOFIELD Acrylic Sealer 25-700. Mix SUPER GRIP into sealer and apply with second coat.

## 6. Cleanup:

Clean tools with A-1 SOLVENT, Acetone or Xylene.

## 7. Maintenance:

Clean sealed surface with water only. Reseal surface as needed but no more than every two years to prevent buildup of sealer.

Meets or Exceeds: ASTM C-309, Type I Class A and B; ASTM C-1315-11; AASHTO Spec M-148; EPA 40 CFR Part D

## 8. Cautions:

Wash skin thoroughly after handling. Use personal protective equipment as required. **IF INHALED:** Move to fresh air. **IF ON SKIN:** Wash with plenty of soap and water. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. If eye irritation persists: Get medical advice/ attention. If skin irritation or rash occurs: Get medical advice/ attention. IF exposed or concerned: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

**KEEP CONTAINER TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. FOR PROFESSIONAL USE ONLY.**

# SCOFIELD® Acrylic Sealer 25-700

Pure acrylic concrete sealers in a solvent base

TECH-DATA BULLETIN TD-XXXX.01

Rev. 01.11.2018



BUILDING TRUST



For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. Read the current actual Safety Data Sheet before using the product. In case of emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Safety Data Sheet which are available online at <http://usa.sika.com/> or at 800-933-7452.

## 9. Warranty:

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of Sika products are subject to Sika's Terms and Conditions of Sale available at <http://usa.sika.com/> or by calling 201-933-8800.

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

SCOFIELD PRODUCTS ARE INTENDED FOR PROFESSIONAL USE ONLY

■ L. M. Scofield Company customer service: 1 800 800 9900

Western Headquarters: 6533 Bandini Blvd., Los Angeles, CA 90040 voice: 323 720 3000 fax: 323 720 3030

Eastern Headquarters: 4155 Scofield Road, Douglasville, GA 30134 voice: 770 920 6000 fax: 770 920 6060

[www.scofield.com](http://www.scofield.com)

© L. M. Scofield Company 2018 - All rights reserved.  
SCOFIELD, , are trademarks of L. M. Scofield Company.