



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

SDS According to GHS OSHA HazCom 29 CFR 1910.1200 and 1272/2008/EC (CLP) amending 1907/2006/EC REACH

1 IDENTIFICATION OF SUBSTANCE/MIXTURE AND OF THE COMPANY UNDERTAKING

1.1 GHS Product Identifier:

Commercial Product Name: **LITHOCHROME® Chemstain™ Classic - 1320: Includes: CS-2 Padre Brown, CS-11 Fern Green, CS-12 Weathered Bronze, CS-13 Copper Patina, CS-15 Antique Amber & CS-16 Faded Terracotta**
Chemical Name: Mixture of metal salts. Various combinations of Chromium III Chloride, Cupric Chloride, Ferric Chloride and Ferrous Chloride in Hydrochloric Acid Solution.

1.2 Relevant identified uses of product:

KEEP OUT OF THE REACH OF CHILDREN!

Product is intended for use only by professionals to chemically stain concrete.

1.3 Details of the supplier of the safety data sheet:

www.scofield.com

L. M. SCOFIELD Company, A SIKA COMPANY Scofield Phone # (800) 800-9900

6533 Bandini Blvd, Los Angeles, CA 90040 Information Phone Number (323) 720-3000 8AM-5PM M-F

4155 Scofield Road, Douglasville, GA 30134 Information Phone Number (770) 920-6000 8AM-5PM M-F

1.4 Transportation Emergency Telephone Number: CHEMTREC (800) 424-9300

2 HAZARDS IDENTIFICATION

2.1 Classification of substance or mixture:

Human Health: GHS and CLP, Irritant, corrosive, poison and toxin, product can cause serious eye damage

Corrosive to metals, Category 1, H290

Acute Toxicity, Oral, Category 2, H301

Acute Toxicity, Dermal, Category 3, H311

Acute Toxicity, skin burns and serious eye damage, Category 1A, 1B, 1C, H314

Acute Toxicity, Inhalation, Category 3, H331

GHS Category Key
1 = Most Hazardous
5 = Least Hazardous

Signal Word: **DANGER**

Chronic Toxicity, STOT, RE, Lungs, Inhalation and skin contact, Category

2.2 Label elements:

GHS Hazard (H) Statements:

H290--May be corrosive to metal

Acute Toxicity

H301--Toxic if swallowed

H311--Toxic in contact with skin

H314--Causes severe skin burns and eye damage



GHS Pictograms



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

Acute toxicity (continued)

H331--Toxic if inhaled

Chronic Toxicity

H372--Causes damage to organs, through inhalation or skin contact, prolonged or repeated exposure.

GHS Precautionary (P) Statements:

Prevention Precautionary Statements

P102--Keep out of the reach of children

P202--Do not handle until all safety precautions have been read and understood

P261--Avoid breathing fume/gas/mist/vapors/spray

P262--Do not get into eyes, on skin, or on clothing

P264--Wash thoroughly after handling

P270--Do not eat, drink or smoke when using this product

P280--Wear protective gloves/protective clothing/ eye protection/ face protection

P284-- In case of inadequate ventilation, wear respiratory protection, see Section 8 PPE

Response Precautionary Statements

P301+P310--**IF SWALLOWED:** Immediately call 911 or a POISON CENTER (800) 222-1222 for first aid advice

P301+P330+P331--**IF SWALLOWED:** rinse mouth, Do NOT induce vomiting.

P302 + P352--**IF ON SKIN:** wash with plenty of water.

P304 + P340--**IF INHALED:** Move person to fresh air, keep comfortable for breathing.

P305 + P351 + P338--**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313--If eye irritation persists, get medical attention.

Disposal Statement

P501--Dispose of contents/container and rinsings in accordance with local, state or federal hazardous material regulations.

2.3 Other hazards: None are known

Refer to Section 16 for wording of terms.

3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Main Constituents:

Solutions of one or more of the following metal salts:Chromium III Chloride, Cupric Chloride, Ferric Chloride, and Ferrous Chloride in Hydrochloric Acid Solution.

The exact compositions of these products are withheld as trade secrets & as confidential business information.



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

3.2 Mixture

Composition of LITHOCHROME® Chemstain Classic by color code

Dangerous Component	CAS No.	Formula	CS-2	CS-11	CS-12	CS-13	CS-15	CS-16
Chromium III Chloride	10025-73-7	CrCl ₃	1-5%	0%	0%	0%	0%	0%
Cupric Chloride	7447-39-4	CuCl ₂	0%	<30%	<30%	<30%	0%	0%
Ferric Chloride	7705-08-0	FeCl ₃	0%	0%	0%	0%	0%	15-40%
Ferrous Chloride	7758-94-3	FeCl ₂	15-40%	<10%	<10%	0%	<20%	5-10%
Hydrochloric Acid	7647-01-0	HCl	5-10%	<10%	<10%	<10%	<10%	0%

4 FIRST AID MEASURES

4.1 Description of first aid measures

Eye Contact: Immediately rinse eyes with plenty of water and for at least 15 minutes, then take person to hospital as soon as possible.

Inhalation: Move person to fresh air and keep comfortable for breathing.

Skin Contact: Remove contaminated clothing and wash skin with soap and water.

Ingestion: May be fatal if swallowed, call 911 or a POISON CENTER (800) 222-1222 immediately for first-aid instructions.

4.2 Most important symptoms and effects both acute and delayed:

If eye contact occurs, quickly rinse eyes with large amounts of fresh water, continue rinsing at least 15 minutes. Blindness can result from single exposure. Have an eyewash station as close as possible to area where product is used. Ingestion will cause burning of mouth and throat along with nausea and vomiting. Call 911 or a POISON CENTER (800) 222-1222 immediately. Prolonged inhalation of fumes will cause irritation of the upper respiratory system and lungs and may result in permanent damage. Repeated or prolonged exposure can cause respiratory tract cancer as well as skin cancer or cancer of other organs.

4.3 Indication of any immediate medical attention and special treatment needed:

If eye contact occurs, immediately flush eyes with water and after flushing eyes thoroughly take person to hospital emergency room. Seek medical attention when experiencing skin or eye irritation, coughing or burning sensation or if not feeling well.

Primary routes of entry:

Eyes, skin, inhalation and ingestion are potential primary routes of entry. Ingestion can be fatal. Eye damage can be permanent in some cases. Breathing mists can cause serious irritation of the upper respiratory tract and lungs.



**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

5 FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Use water spray or dry extinguishing media that is suitable for fires in surrounding areas. Acidic metal solution is not combustible. May contain oxidizers. Keep away from combustible materials and strong bases.

5.2 Special Hazards arising from the substance or mixture

Acid solutions have a very low pH and can cause corrosion of some metals to produce hydrogen gas which is highly explosive.

5.3 Advice for firefighting:

Use water spray to keep containers cool. Avoid contact with strong bases which can react dangerously with high exotherm (heat build-up).

Firefighters should wear full protective clothing including self-contained breathing equipment.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions

General measures

Have emergency spill containment materials available. Do not permit discharge of product or product rinsings into any waterways or soil area. Neutralize spills with pulverized limestone, soda ash or sodium bicarbonate (baking soda). Use non-combustible and acid resistant absorbent to contain spill.

Dispose of the product and absorbent material in hazmat containers or drums. (Refer to P501 in sec. 2).

Protective equipment

Wear appropriate safety equipment, eye and face protection, chemically resistant gloves and apron or coat

6.2 Environmental precautions

Product is very toxic to fish and other water species. Do not release product into sewers, waterways or soil.

Contain spills with absorbent and avoid release of any product rinsings into sewers, waterways or soils.

6.3 Methods and material containment and cleaning up:

Contain spills using dikes and/or absorbent materials, such as clays or dry earth. Avoid combustible absorbents.

Use a shovel to collect and handle absorbed hazardous waste from spills. Use an acid resistant drum for disposal.



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Product is for professional use only. Store product in original containers in a cool dry and shaded area off of ground. Keep product away from children and animals. Open container slowly and carefully while wearing the proper safety equipment. Keep children and animals away from work area during use of product and afterwards until clean-up is complete.

7.2 Conditions for safe storage including any incompatibilities

Product is not compatible with most common metals, including aluminum, magnesium, iron and most steel products. Check compatibility of application equipment before use. Storage of product in the sun can cause heating and pressure build-up in the container. Keep product in shade.

7.3 Specific end uses

Product is intended for use only by professionals to color concrete and similar cementitious materials.

8 EXPOSURE CONTROL/PERSONAL PROTECTION

8.1 Control parameters

Chemical Name	ACGIH TLV	OSHA PEL 8hr	OSHA TWA	NIOSH REL-TWA	Weight %
Chromium III Chloride	0.5 mg/m ³	0.5 mg/m ³	NDA	0.5 mg/m ³	0-5%
Cupric Chloride	NDA	NDA	NDA	0.5 mg/m ³	0-30%
Ferric Chloride	1 mg/m ³	1 mg/m ³	NDA	0.5 mg/m ³	0-40%
Ferrous Chloride	1 mg/m ³	1 mg/m ³	NDA	0.5 mg/m ³	0-40%
Hydrochloric Acid	2 ppm	5 ppm	7 mg/m ³	NDA	0-10%

NDA = No data Available

8.2 Exposure controls:

Engineering measures:

Use only with adequate ventilation. Keep worker exposure of airborne contaminants below agency/statutory limits.

8.3 Individual protective measures:

Eye protection: Wear tight-fitting chemical splash goggles to protect eyes.

Respiratory equipment: In case of inadequate ventilation, wear a properly fitted respirator with acid gases canisters and mist filters.

Hand protection: Wear chemical resistant (neoprene) impervious gloves to protect hands from product.

Skin protection: Wear a chemical resistant rubber apron or rubber jacket and boots to protect skin from contact with product.

Personal Protective Equipment

Respirator selection: acid gas+mist filters, P100, N95



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

8.3 Individual protective measures (continued):

Hygiene measures: Minimize exposure in accordance with good hygiene practice. Wash with soap and water after handling product.

Environmental exposure controls: Provide eyewash stations close to work areas and adequate ventilation when using this product.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information of basic physical and chemical properties

	Physical State/Property	Value/Result
a)	Appearance	colored liquid
b)	pH	< 3.0
c)	Color	various colors
d)	Odor	pungent acid
e)	Flash Point	will not flash
f)	Explosive Limits, Lower	not applicable
g)	Explosive Limits Upper	not applicable
h)	Boiling Point	212 °F (100 °C)
i)	Flammability	not applicable
j)	Relative Density-sp gr, water = 1.0	1.1 to 1.5
k)	Solubility in water	soluble
l)	Viscosity	similar to water
m)	VOC g/L	0.0 g/L (0.0 lb/gal)

9.2 Other information: No other information is available.

10 STABILITY AND REACTIVITY

10.1 Reactivity

Reacts vigorously with strong bases liberating heat.

10.2 Chemical stability

Product is stable when stored at moderate temperatures and in shaded areas out of direct sunlight.

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur. Reacts rapidly with strong bases causing heat build up.



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

10.4 Conditions to avoid

Avoid heat and direct sunlight.

10.5 Incompatible materials

Keep away from strong bases which can react vigorously liberating heat. Contact with some metals (aluminum, magnesium and iron) can form hydrogen gas which is potentially explosive in mixtures with air.

10.6 Hazardous decomposition products:

Product can decompose at high temperatures to form hydrochloric acid fumes. These fumes are highly toxic and corrosive. High storage temperatures can cause decomposition to form toxic chlorine gas.

11 TOXICOLOGICAL INFORMATION

Chemical Name	LD ₅₀ Rat Oral	LC ₅₀ Inhalation Rat	LD ₅₀ Other Exposure Route	
Chromium III Chloride	440 mg/kg	no data available	no data available	
Cupric Chloride	584 mg/kg	no data available	>2000 mg/kg dermal rat	
Ferric Chloride	*1300 mg/kg	no data available	>2000 mg/kg dermal rabbit	*mouse
Ferrous Chloride	450 mg/kg	no data available	no data available	
Hydrochloric Acid	700 mg/kg	3124 ppm/1 hr (rat)	900 mg/kg oral rabbit	

11.1 Principal routes of entry:

Ingestion: May be fatal if swallowed. Causes chemical burns to mouth, throat and stomach. Causes vomiting, nausea and diarrhea. Aspiration of material into lungs may cause chemical pneumonia, which can be fatal.

11.2 Skin Contact:

Corrosive. Causes severe skin irritation and chemical burns, resulting in permanent scarring or even death.

11.3 Inhalation:

Corrosive to the respiratory system. Causes irritation of respiratory tract, chest pain, and coughing. Vapors may cause pulmonary edema.

11.4 Eye contact:

Vapors are corrosive to eyes. Concentrated vapor, mist or splashes can cause severe irritation, burns and permanent blindness.

11.5 Specific effects:

Specific effects: Prolonged or repeated exposure can cause chronic bronchitis, redness, swelling, and pain.



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

11.6 Chronic Toxicity:

This product contains one or more components that have been reported to be carcinogens based on IARC, OSHA, ACGIH or NTP classifications.

Teratogenicity: May alter genetic material

Mutagenicity: Investigated as a mutagen

Embryotoxicity: May cause reproductive disorders

Specific Target Organ Toxicity, STOT, RE, lungs, skin and other organs

Specific sensitizing, can cause contact dermatitis or contact eczema

12 ECOLOGICAL INFORMATION

12.1 Toxicity	Aquatic Toxicity Fish			Aquatic Toxicity Invertebrates		
	LC ₅₀	Species	Interval	EC ₅₀	Species	Interval
Chromium III Chloride	15.4 mg/L	Cyprinus Carpio	96 hr	9.108 mg/L	Daphnia magna	48 hr
Cupric Chloride	0.12-0.23 mg/L	Cyprinus Carpio	96 hr	0.04 mg/L	Daphnia magna	48 hr
Ferric Chloride	21.84 mg/L	Pimphales Promolas	96 hr	9.6 mg/L	Daphnia magna	48 hr
Ferrous Chloride	4 mg/L	Morone saxatilis	96 hr	17 mg/L	Daphnia magna	48 hr
Hydrochloric Acid	282 mg/L	Gambusia affinis	96 hr	0.45 mg/L	Daphnia magna	48 hr

Ecotoxicity: Toxic to aquatic organisms. May cause long-term effects in the aquatic environment.

12.2 Persistence and degradability

Components are persistent and are not degradable.

12.3 Bioaccumulative potential

No data is available.

12.4 Mobility in soil:

Mobility: No additional information is available.

Results of PBT and vPvB: Not applicable for inorganic materials.

PBT and vPvB: No additional information is available.

Other Adverse affects: None are known.

13 DISPOSAL CONSIDERATIONS

13.1 Disposal P501-Dispose of contents/container in accordance with applicable local/state/federal regulations.



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

14 TRANSPORT INFORMATION

USDOT

14.1 UN Proper shipping names

CS-2 Padre Brown, DOT/IMDG/IATA: UN3264, Corrosive, liquid, acidic, inorganic, n.o.s.,(iron dichloride, hydrochloric acid), 8, II.
CS-11 Fern Green and CS-13 Copper Patina, DOT: UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (copper dichloride, hydrochloric acid), 8, II. / IMDG/IATA: UN3264 Corrosive liquid, acidic, inorganic, n.o.s., (copper dichloride, hydrochloric acid), 8, II. MARINE POLLUTANT
CS-12 Weathered Bronze, DOT: UN3264, Corrosive liquid, acidic, inorganic, n.o.s.,(copper dichloride, iron trichloride), 8, II. / IMDG/IATA UN3264 Corrosive, liquid, acidic, inorganic, n.o.s., (copper dichloride, iron trichloride), 8, 11. MARINE POLLUTANT
CS-15 Antique Amber, DOT/IMDG/IATA: UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (iron dichloride, hydrochloric acid), 8, II.
CS-16 Faded Terracotta, DOT/IMDG/IATA: UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (iron trichloride, iron dichloride), 8, II.

14.2 Transport Hazard Class Hazard Class 8 Corrosive

14.3 Packing Group PG II

14.4 Environmental Hazards

CS-11, CS12 and CS-13 are marine pollutants and are environmentally hazardous substances.

14.5 Special Precaution for user: Corrosive

14.6 Transport in bulk according to Annex II MARPOL 73/78 and IBC Code: Not applicable.



15 REGULATORY INFORMATION

15.1 Safety, health, environmental regulations/legislation specific for the substance or mixture.

OSHA HazCom 2012, 29 CFR 1910.1200 and regulation (EC) No. 1272/2008 CLP of the European Parliament

There are no TSCA 12b chemicals in this product.

req. = requirement

REPORTING REQUIREMENTS for SARA TITLE III					
Product Ingredients	SARA III	Acute Health Hazard	Chronic Health hazard	Reactivity Hazard	Title III
dangerous components	Section 303	Section 311/312	Section 311/312	Section 311/312	Sec 313
Cupric Chloride	not listed	not listed	not listed	not listed	listed
Ferric Chloride	not listed	not listed	not listed	not listed	no req.
Ferrous Chloride	not listed	listed	listed	not listed	no req.
Hydrochloric Acid	not listed	listed	not listed	not listed	listed

Check with the appropriate state or local agency for regulatory information.

RCRA Hazardous Waste: Characteristic Corrosive Liquid (Liquid with a pH <2.0)

Clean Air Act Listed as a Hazardous Air Pollutant (Hydrochloric Acid)



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**LITHOCHROME® Chemstain™ Classic - 1320,
CS-2 Padre Brown, CS-11 Fern Green,
CS-12 Weathered Bronze, CS-13 Copper Patina,
CS-15 Antique Amber & CS-16 Faded Terracotta**

15.2 Chemical Safety Assessment

Right-to-Know States, Massachusetts, Pennsylvania, and New Jersey, Hydrochloric Acid, Copper Chloride, Ferrous Chloride and Ferric Chloride

For labeling information go to section 2.

There are no TSCA 12b chemicals in this product.

16 OTHER INFORMATION


The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Wording of terms:

- ACGIH American Conference of Government Industrial Hygienists.
- CAS No. Chemical Abstract Service, a unique number for each chemical
- CERCLA Comprehensive Environmental Response, Compensation and Liability Act
- CLP Classification, Labeling and Packaging, EC 1272/2008
- EC₅₀ Effective Concentration that causes 50% mortality of population.
- EINECS European Inventory of Existing Commercial Chemical Substances (EU)
- GHS Global Harmonization System
- HazCom Hazard Communication
- IARC International Agency for Research on Cancer
- LC₅₀ Lethal Concentration that results in 50% mortality of Population
- LD₅₀ Lethal Dose that results in 50% mortality of Population
- MARPOL International Convention for the Prevention of Pollution from Ships
- NFPA National Fire Prevention Association
- NIOSH National Institute for Occupational Safety and Health
- OSHA Occupational Safety & Health Administration
- PEL Permissible Exposure Limit
- RCRA Resource Conservation and Recovery Act
- RE Repeated Exposure
- REACH Registration, Evaluation, Authorization & Restrictions of Chemicals, EC/1907/2006
- REL Recommended Exposure Limit
- RQ Reportable quantity
- SARA III Superfund Amendments and Reauthorization Act
- SDS Safety Data Sheet (GHS replacement for MSDS)

Hazmat Identification System	
Health Hazard	3
Fire Hazard	0
Reactivity Hazard	1
Personal Protection	see sec 8

0=minimal hazard, 4=extreme hazard



California Prop 65: Warning! This Product contains one or more chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Safety Data Sheet & Warranty



BUILDING TRUST




L. M. Scofield Company - A SIKA COMPANY

LITHOCHROME® Chemstain™ Classic - 1320, CS-2 Padre Brown, CS-11 Fern Green, CS-12 Weathered Bronze, CS-13 Copper Patina, CS-15 Antique Amber & CS-16 Faded Terracotta

Wording of terms: (continued)

STOT	Specific Target Organ Toxicity
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
US DOT	United States Department of Transportation
VOC	Volatile Organic Compounds
WHMIS	Workplace Hazardous Materials Information System (Canada)



The details in this document are based on our current knowledge and experience and are only for this product and only in regard to safety requirements.

Before using, read Scofield's Tech-Data Bulletin TD-1320 for this product, the complete package label and this SDS and Warranty.

SDS issue date: July 6, 2015, Revised September 8, 2016 added SIKA COMPANY Trademark. Revised 6/2/2017 Chemstain Classic CS-16 Faded Terracotta UN number changed to UN 3264. Revised Section 14 Jan 11, 2018

END OF SDS

LIMITED WARRANTY

Since no control is exercised over product use, L. M. Scofield Company (Scofield) represents and warrants only that its products are of consistent quality within manufacturing tolerances. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESS OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SCOFIELD, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Liability for breach of contract, negligence, or on any other legal basis is limited to the lesser of refund or replacement of defective materials. SCOFIELD WILL NOT BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING FOR DELAYS OR LOST PROFITS. Communication of this warranty and its limitations to end users is not the responsibility of Scofield, but should be communicated by those in direct contract with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. The end user shall determine the suitability of the products for the intended use and assumes all risks and liability in connection therewith.