



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

SDS according to GHS OSHA 29 CFR 1910.1200 and 1272/2008/EC (CLP) amending 1907/2006/EC (REACH)

**1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY UNDERTAKING**

**1.1 GHS Product Identifier**

**Commercial Product Name:** Tint Cups (Part A) for: LITHOCHROME® Tintura Stain™-7350, COLORCURE® Concrete Curing and Sealing Compound - 1690 and LITHOCHROME® Colorwax™ Concrete Concrete Curing Compound - 1590

**1.1 GHS Product Identifier**

**Chemical Name:** Water-based dispersions of inorganic or organic pigment mixtures.

**1.2 Relevant identified uses of product:** Tint cups are color additive, Part A components for: LITHOCHROME® Tintura Stain™, COLORCURE® Concrete Curing Compound and Sealer and LITHOCHROME® Colorwax™ Concrete Curing Compound -1590 SCOFIELD products are intended for use by professionals. KEEP OUT OF THE REACH OF CHILDREN.

**1.3 Details of the supplier of the safety data sheet:**

**L. M. SCOFIELD Company**

6533 Bandini Blvd, Los Angeles, CA 90040

4155 Scofield Road, Douglasville, GA 30134

**Scofield Phone #: (800) 800-9900**

[www.scofield.com](http://www.scofield.com)

Information Phone Number (323) 720-3000 M-F 8AM-5PM

Information Phone Number (770) 920-6000 M-F 8AM-5PM

**1.4 Transportation Emergency Telephone Number: CHEMTREC (800) 424-9300**

**2 HAZARDS IDENTIFICATION**

**2.1 Classification of substance or mixture:**

GHS-US Hazard classification

Skin irritant, STOT, SE, H313, Category 5

Eye irritant, STOT, SE, H320, Category 2

Human Health: Product can damage eyes. Avoid getting product into eyes. Product can irritate skin.

Environment: Product is not considered to be dangerous to the environment.

**2.2 Label elements:**

**GHS Hazard (H) Statements**

**Acute toxicity**

H313--May be harmful in contact with skin

H320--Causes eye irritation

**GHS Precaution (P) Statements:**

**Prevention precautionary statements**

P280--Wear protective gloves/eye protection

P284--Wear respiratory protection



GHS Pictogram

GHS Signal Word: **NONE**



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

**Response precautionary statements**

P305+P351+P338--**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contacts if present and easy to do. Continue rinsing.

P337+P313--If eye irritation persists, get medical attention

**Disposal precautionary statements**

P501--Dispose of contents/container in accordance with applicable local/state/regional/federal regulations

**2.3 Hazards not otherwise classified (HNOC) or not covered by GHS:** No other hazards are known.

Refer to Section 16 for wording of terms.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Various Metal Oxide Pigments

**3.2 Mixture:**

Components of Mixture, Formula	CAS #	EINECS #	Weight %
Proprietary pigment dispersant	CBI	CBI	0-5%

The exact percentages in this composition have been withheld as a trade secret and as confidential business information.

**4 FIRST AID MEASURES**

**4.1 Description of first aid measures:**

**Eye Contact :** Quickly flush with plenty of clean water for 15 minutes. Remove contact lenses if easy to do. Open eyelids widely during flushing. If irritation persists, transport person to emergency room and bring these instructions for doctor. Provide easy access to eye wash station in work area.

**Inhalation:** Move person to fresh air, make comfortable for breathing. Get medical attention if condition worsens.

**Skin Contact:** May result in skin irritation. Remove contaminated clothing. Wash skin with soap and water.

**Ingestion:** May cause irritation of mouth, throat, esophagus and gastrointestinal tract. Do not induce vomiting. Give large amounts of water. Call 911 or a POISON CENTER (800) 222-1222. Get immediate medical attention if needed.

**4.2 Most important symptoms and effects both acute and delayed:**

Eye contact can cause irritation. If irritation persists after rinsing eyes, take person to emergency room for treatment and bring these instructions (SDS) for doctor.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Refer to SECTION 11 for more detailed information on health effects and symptoms.

Primary routes of entry include: Eye Contact, Skin Contact, Ingestion, Inhalation of spray



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

**5 FIRE-FIGHTING MEASURES**

**5.1 Extinguishing media:** Use fire extinguishing media appropriate for surrounding fire.

**5.2 Special Hazards arising from the substance or mixture:**

- Fire Hazard: Not flammable
- Explosion Hazard: No explosion hazard
- Reactivity: Hazardous reactions will not occur.
- Other Hazards: Spills can be slippery, exercise care to avoid slipping

**5.3 Advice for fire-fighting:** Use normal fire fighting equipment.

**6 ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions :**

- General measures: Use personal protective equipment. See section 8 for additional information.
- Protective equipment: Wear suitable protective clothing with eye protection and gloves.

**6.2 Environmental precautions:**

Avoid discharge into waterways, sewers and soil. If spill enters water, contact local authorities.

**6.3 Methods and material containment and cleaning up:**

Method of cleaning up: May be slippery. Use caution. Contain spill with absorbent materials. Collect with a wet vacuum.

**7 HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

Always wash hands immediately after handling product. Do not eat or drink in area where product is being used.

**7.2 Conditions for safe storage including any incompatibilities:**

Do not allow product to freeze.

**7.3 Specific end uses:**

This product is intended for use only by professionals to add color and shading for new or existing architectural concrete.




**8 EXPOSURE CONTROL/PERSONAL PROTECTION**

Components of Mixture, Formula	Exposure Limits TWA	
	ACGIH TLV	OSHA PEL 8hr
No hazardous components.	none	none
Proprietary pigment dispersant	CBI	CBI

**8.1 Control Parameters**

Usually not required.

**Personal Protective Equipment**

Respirator Selection: Organic vapors + mists, P100 or N95



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

**8.2 Exposure controls:**

Engineering measures: Provide local exhaust and adequate ventilation in work area.

**8.3 Individual protective measures:**

- Eye protection: Wear tight-fitting goggles or safety glasses with side shields to protect eyes.
- Skin protection: Wear chemical resistant rubber gloves to protect hands.
- Respiratory Protection: If in a confined area, wear a respirator fitted with organic vapors and particulate/mists.
- Hygiene measures: Wash hands after exposure, Remove contaminated clothing, shower and wash skin with plenty of soap and water. Wash contaminated clothing prior to reuse.
- Environmental exposure controls: Provide eye wash stations and emergency showers near work area.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information of basic physical and chemical properties**

Property-Test	Value/Result
a) pH	8 to 10
b) Color	various colors
c) Odor	low odor
d) Freezing/Melting Point	32 °F (0 °C)
e) Boiling Range	212 °F (100 °C)
f) Flash Point	not applicable
g) Auto ignition Temperature	not applicable
h) Explosive Limits UEL	not applicable
i) Explosive Limits LEL	not applicable
j) Flammability (solid, gas)	not flammable
k) Vapor Pressure	not applicable
l) Vapor density vs air = 1.0	not applicable
m) Density	not applicable
n) Solubility in water	dispersed pigments are not soluble
o) KOW Partition Coefficient	not applicable
p) Evaporation Rate	not applicable
q) Viscosity	not applicable
r) VOC	< 50 g/L (<0.42 lb/gal)

**9.2 Other information**

Other data: Specific Gravity, water = 1.0 1.8 - 2.2



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

**10 STABILITY AND REACTIVITY**

<b>10.1 Reactivity:</b>	Not reactive
<b>10.2 Chemical stability:</b>	Product can react with strong acids.
<b>10.3 Possibility of hazardous reactions:</b>	Hazardous reactions will not occur.
<b>10.4 Conditions to avoid:</b>	Avoid contact with strong acids
<b>10.5 Incompatible materials:</b>	Strong acids
<b>10.6 Hazardous decomposition products:</b>	Pigment dispersion does not decompose under moderate conditions.

**11 TOXICOLOGICAL INFORMATION**

**Toxicological results of testing**

Components of Mixture, Formula

No hazardous components are present

a) acute toxicity,	Not classified as acutely toxic material.
b) skin corrosion/irritation,	Pigment dispersions can cause skin irritation from mechanical irritation.
c) eye damage/irritation,	Pigment dispersions can cause eye damage (as a mechanical irritant, do not rub eyes).
d) respiratory or skin sensitization,	Not classified as a respiratory sensitizer or skin sensitizer.
e) germ cell mutagenicity	Product does not cause germ cell mutagenicity.
f) carcinogenicity by agency:	All components of this product, present at 0.1% or greater and not identified by OSHA ACGIH, or ACGIH as probable, possible or confirmed carcinogens.
g) reproductive toxicity,	Product does not cause or contribute to reproductive toxicity.
h) STOT-single exposure,	Product can cause serious eye damage.
i) STOT-repeated exposure,	No chronic effects are known
J) aspiration hazard,	If ingested, do NOT induce vomiting. Product can be aspirated if vomiting occurs.

<b>11.1 Inhalation:</b>	Product may irritate throat and respiratory system and cause coughing.
<b>11.2 Skin contact:</b>	Product may have an irritating effect on moist skin.
<b>11.3 Eye contact:</b>	Splashes from liquid pigment mixture can cause serious eye damage. Immediate first aid is required, followed by emergency medical attention.
<b>11.4 Ingestion:</b>	Ingestion may cause severe irritation of the mouth, esophagus and gastrointestinal tract.
<b>11.5 Specific effects:</b>	No other specific effects are known.



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350,  
COLORCURE® Concrete Curing Compound and Sealer - 1690 and  
LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

**12 ECOLOGICAL INFORMATION**

**12.1 Toxicity:**

Product is not considered to be toxic.

Ecotoxicity: This product is not expected to be hazardous to the environment.

**12.2 Persistence and degradability:**

Degradability: Product is not degradable.

**12.3 Bioaccumulative Potential:**

Bioaccumulative Potential No information is available on bioaccumulative potential.

**12.4 Mobility in soil:**

Mobility: No information is available on mobility in soil.

Results of PBT and vPvB assessment Mixture is not relevant for PBT or vPvB assessment.

Other adverse affects: No other adverse effects are known.

**13 DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

GHS P501-Dispose of contents/container according to local/state/regional/federal waste regulations.

**14 TRANSPORT INFORMATION**

**This product is not covered by international regulation of the transport of dangerous goods.**

DOT: Not regulated

**14.1 UN Number:** Not regulated

**14.2 UN proper shipping name:** Not classified as dangerous goods under DOT and UN regulations.

**14.3 Transport hazard class(es):** Not regulated

**14.4 Packing group:** Not regulated.

**Packaging group:** Not regulated

**14.5 Environmental hazards**

Marine pollutant: Not regulated.

Environmentally hazardous substance: Not applicable.

**14.6 Special precautions for user:** None are known.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and IBC Code:** Not regulated.



BUILDING TRUST



L. M. Scofield Company - A SIKA COMPANY

**Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

**15 REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for substance or mixture.**

OSHA HazCom 2012, 29 CFR 1910.1200 and regulation (EC) No. 1272/2008 CLP of the European Parliament

**15.2 Chemical Safety Assessment:** Not required.

For information on labeling refer to section 2

There are no TSCA 12b chemicals in this product

**16 OTHER INFORMATION**


**Before using, read Scofield Tech-Data Bulletin TD-8830 for this product, the complete package label & this SDS & Warranty.**

**Wording of terms:**

- ACGIH American Conference of Government Industrial Hygienists
- CAS No. Chemical Abstract Service
- CLP Classification, Labeling and Packaging, EC 1272/2008
- EC<sub>0</sub> High concentration that has no mortality of population
- EINECS European Inventory of Existing Commercial Chemical Substances (EU)
- GHS Global Harmonization System, worldwide chemical safety system
- IARC International Agency for Research on Cancer
- HazCom Hazard Communication, GHS US CFR 29 1910.1200
- LC<sub>0</sub> Highest Concentration with no mortality of population
- LC<sub>50</sub> Lethal Concentration for population at 50% mortality
- LD<sub>50</sub> Lethal Dose for population at 50% mortality
- MARPOL International Convention for the Prevention of Pollution from Ships
- NFPA National Fire Protection Association
- NIOSH National Institute for Occupational Safety and Health
- OSHA Occupational Safety and Health Administration
- PBT Persistent, Bioaccumulative and Toxic
- PEL Permissible Exposure Level
- RE Repeated Exposure
- REACH Registration, Evaluation, Authorization and Restrictions of Chemicals, EC/1907/2006
- REL Recommended Exposure Limit
- SDS Safety Data Sheet (GHS replacement for MSDS)
- SE Single Exposure
- STOT Specific Target Organ Toxicity
- TLV Threshold Limit Value

Hazardous Material Information	
Health Hazard	1
Flammability Hazard	0
Physical Hazard	0
Personal Protective Equipment	See sec. 8 PPE

0=minimal hazard. 4 = extreme hazard



NFPA: 0 = low hazard, 4 = high hazard

**California Prop 65 Warning: This product contains one or more chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.**

## Safety Data Sheet & Warranty



**BUILDING TRUST**




L. M. Scofield Company - A SIKA COMPANY

### **Color Additive (Part A) for: LITHOCHROME® Tintura Stain -7350, COLORCURE® Concrete Curing Compound and Sealer - 1690 and LITHOCHROME® Colorwax™ Concrete Curing Compound - 1590**

#### **Wording of terms:** (continued)

TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
US DOT	United States Department of Transportation
VOC	Volatile Organic Compound
vPvB	Very Persistent and Very Bioaccumulative
WHMIS	Workplace Hazardous Materials Information System (Canada).



The details in this document are based on our current knowledge and experience and are only for this product and only in regard to safety requirements.

SDS issue date: July 20, 2015. Revised September 27, 2016 2016 added SIKA COMPANY Trademark.

**END OF SDS**

#### LIMITED WARRANTY

L. M. Scofield Company (Scofield) represents and warrants only that its products are of consistent quality and within manufacturing tolerances. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESS OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SCOFIELD, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Liability for breach of contract, negligence, or on any other legal basis is limited to the lesser of refund or replacement of defective materials. SCOFIELD WILL NOT BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING FOR DELAYS OR LOST PROFITS. Communication of this warranty and its limitations to end users is not the responsibility of Scofield, but should be communicated by those in direct contract with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. The end user shall determine the suitability of the products for the intended use and assumes all risks and liability in connection therewith.