

# SCOFIELD® Revive™

Exterior Concrete Stain

## Contractor Sheet

---

**Scofield Revive Exterior Concrete Stain is a semi-opaque, pigmented, ready-to-use solvent-based penetrating polysiloxane stain designed to add new color to uncolored concrete, or to renew color intensity and uniformity to aged, weathered, or patched, concrete surfaces. It is ideal for unifying the appearance of partial slab replacements, patches, job continuations, or slabs of different composition or mix design.**

### Colors:

- Available in 20 popular colors to approximate those depicted on Revive color chart CC-1770.
- “Make to Order” and custom color matching is also available.

### Packaging:

- Single component, available in 1 gallon and 5 gallon pails.

### Coverage:

- Typically 100-300 ft<sup>2</sup>/gal. depending on the porosity of the concrete.
- SCOFIELD Revive Exterior Concrete Stain must be applied full strength without thinning.

### Ideal uses:

- Add color to uncolored concrete or concrete pavers.
- Impart a consistent appearance to mismatched colors.
- Revitalize faded, worn color.

### Application:

- Apply with an acetone-resistant sprayer.
- May also be applied with a brush or roller with the appropriate nap. In most circumstances a 3/4 inch nap will give the best results.
- Before applying stain, surfaces must be made porous, and be dry, and clean of all prior sealers, curing compound, oils, or other foreign materials that might prevent penetration or adhesion.
- Surface must meet a Concrete Surface Profile (CSP) of 1, as determined by the International Concrete Repair Institute, (ICRI), Alexandria, VA.

1-800-800-9900

[www.scofield.com](http://www.scofield.com)

© 2018 Scofield, A Business Unit of Sika Corporation.

 **SCOFIELD**

**BUILDING TRUST**



# Semi-Opaque Exterior Concrete Stain

## SCOFIELD® Revive™

### Exterior Concrete Stain

#### Keys to success:

- Prior to application, grind, acid etch, power wash, or scrub surfaces with stiff bristle brushes and strong detergents to remove undesired materials and any loose concrete laitance that may harm adhesion.
- Allow four to eight hours drying time before permitting foot traffic. Drying time will depend on temperature and surface porosity. Allow stain to cure a minimum of four days before applying sealers or topcoats.
- Do not pressure wash or use aggressive cleaning methods for two weeks after application.

#### Sealing and maintenance:

- For increased stain resistance, and defense against aggressive cleaning practices, topcoat with a quality Scofield sealer such as CEMENTONE® Clear Concrete Sealer, SCOFIELD® Cureseal-W™, SCOFIELD® Selectseal Plus™, or SCOFIELD® Repello® FPS.



Prior to beginning the job, consult the appropriate Scofield Tech-Data Bulletin SCOFIELD Revive Exterior Concrete Stain TD-1770.



1-800-800-9900  
[www.scofield.com](http://www.scofield.com)

© 2018 Scofield, A Business Unit of Sika Corporation.

 SCOFIELD

BUILDING TRUST

 Sika®